

DATA SHEET



Power Supply





AC Mains and/or 3V Lithium Battery











MODEL: RSDUALP


Key Information


Product or component Device application

Sensor type Colour Quantity Packaging type Smoke Alarm Early Detection of Smouldering Fires and Open Fires Photoelectric Sensor

White Carton

Alarm unit: Ø 140mm





promise the products contained herein. This documentation is not intended as a substitute for and is not to be
used for determining suitability of reliability of these products for specific user applications. It is the duty of any such
user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with
respect to the relevant specific application or use thereof. Neither Red Smoke Alarms PTY. LTD nor any of its affiliates
or subsidiaries shall, be responsible or liable for misuse of the information contained herein.

1 Ower Supply	Ao Hains and/or ov Eleman Baccery
Rated Supply Voltage	220240Vac
Backup Type	3V Lithium Battery (When on AC Mains)
Battery Life	10 YR
Output Voltage Limits	Interconnected: 9V
	Low Battery: 2.7V
Detection Type	Smoke
Function	Hush Function
	Smoke Detection
	Local Alarm
Control Type	Button for Test/ Hush Function
Number of Devices	Hard Wired Interconnected up to 40 Pieces
Operating Distance for Hard Wired Interconnected	150M in Free Field
Response Time	Approx. 8 SEC
Noise Level	85 dB at 3M Minimum
Time Delay Range	10 MIN: for Hush
	10 HR: for Silence
	72 HR: for Memory Function
Local Signal	Sound: Alarm
	Sound: Signal Visual: 1 LED (Red) for Warning, Low Battery,
	Fault and Memory Function
	Visual: 1 LED (Green) when AC Mains is ON
Type of Installation	Indoor
Device Mounting	Surface
Mounting Support	Wall-mount, Ceiling
Fixing Type	By Screws
Alarm Diameter	140 MM
Protrusion from Ceiling	49 MM
Wireless Compatibiliity	Compatible with RFMOD (Wireless Module)
Transmission Frequency	Radio Frequency 433.92 MHz
Number of Devices	Wireless Interconnected up to 20 Pieces
Operating Distance for	30M Indoor Use Line of Sight
Wireless Interconnected	100M in Free Field
Ambient Air Temperature for Operation	045°C
Relative Humidity	595%
Product Certifications	CSIRO
Standards	AS 3786:2014+A1:2015+A2:2018

