



ECOGEM S9041TC - 10W

Dimmable 10 watt LED downlight, with selectable CCT, IP44

Application

Ideal for any residential or commercial interior space

Design Specifications

- Selectable CCT 3000K/4200K/5700K
- IC - 4 rated, durable die-cast aluminium body profile
- Choice of White or Black powder coat finish or Satin Nickel
- Remote trailing edge dimmable, flickerCONTROLLED LED driver, with flex and plug
- High efficiency LED optics CRI90, with an opal polycarbonate diffuser
- White surface mount options available, colour trim options: Black (S9041 BK RING), Silver (S9041 SL RING)








NEED A HAND
PACKING YOUR
PRODUCT DATA
SHEETS?
GIVE THE SAL
SHOPPING CART
A GO.

Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge, optional 1-10V, DALI / DSI**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9041 TC WH	240	10	850/1000/900	3000/4200/5700	90
	S9041 TC SN	240	10	850/1000/900	3000/4200/5700	90
	S9041 TC BK	240	10	800/950/850	3000/4200/5700	90
	S9041 BK RING					
	S9041 SL RING					

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)	IPART
YES	90	WHITE	92	103	40(H)	YES
YES	90	SATIN NICKEL	92	103	40(H)	YES
YES	90	BLACK	92	103	40(H)	
	90	BLACK				
	90	SILVER				


REES
YES
YES

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



Dimensions





Photometric Data

Unit: cd C0/C180 — C30/C210 —
cd C60/C240 — C90/C270 —

S9041 TC at 3000K

